

Marshall

BROADCAST & PRO AV

CV605-U3 CV605-U3W

5x HD60 IP PTZ Camera

| | |
|----------------------------------|--|
| Model | CV605-U3, CV605-U3W |
| Camera Parameter | |
| Optical Zoom | 5X, f=3.1~15.5mm |
| Sensor | 1/2.8-inch-high quality HD CMOS sensor |
| Effective Pixels Video Format | 16:9, 2.07 megapixe |
| | USB: YUY2, NV12: 640x480/320x180/480x270/640x360/800x448/800x600/1024x576/ 1280x720/1920x1080 MJPEG, H.264: 640x480/320x240/352x288/480x270/640x360/720x480/720x576/ 800x448/800x600/960x540/1024x576/1280x720/1600x896/1920x1080 HDMI: 1080P 60/59.94/50/30/29.97/25; 720P 60/59.94/50; |
| Viewing Angle | 16.43°(tele)--83.7°(wide) |
| Digital Zoom | 10X additional |
| Minimum Illumination | 0.5Lux (F1.8, AGC ON) |
| DNR | 2D & 3D DNR |
| White Balance | Auto / Manual/ One Push/ VAR |
| Focus | Auto/Manual/One Push |
| Iris | Close/F11/9.6/8.0/6.8/5.6/4.8/4.0/3.4/2.8/2.4/2.0/1.8 |
| Electronic Shutter | Auto/Manual |
| BLC | ON/OFF |
| Video Adjustment | Brightness, Color, Saturation, Contrast, Sharpness, B/W mode, Gamma curve |
| SNR | >55dB |
| Input/ Output Interface | |
| Video Interfaces | USB3.0 Type-C, HDMI, LAN |
| Video Compression Format | H.264, YUV2, NV12, MJPEG |
| Audio Input Interface | Two-channel 3.5mm (Line and Mic level) |
| Audio Output | USB3.0, HDMI, LAN output together with video |
| Audio Compression Format | AAC/MP3/G.711A |

| | |
|------------------------|--|
| IP Interface | 100M IP port (100BASE-TX) |
| Network Protocol | RTSP/RTMP, ONVIF; Support IP Visca control protocol |
| Control Interface | RS232 |
| Control Protocol | VISCA/Pelco-D/Pelco-P; Baud Rate: 115200/38400/9600/4800/2400 |
| Power Interface | HEC3800 outlet (DC12V) |
| Supply Adapter | AC110V-AC220V to DC12V/1.5A |
| Input Voltage | DC12V±10% |
| Input Current | 1A (Max) |
| Consumption | 12W (Max) |
| PTZ Parameter | |
| Pan Rotation | 340-degree pan range |
| Tilt Rotation | 180-degree tilt range |
| Pan Control Speed | 0.1 -60°/sec |
| Tilt Control Speed | 0.1-30°/sec |
| Preset Speed | Pan: 60°/sec, Tilt: 30°/sec |
| Preset Number | 255 presets (10 presets by remote controller) |
| Other Parameter | |
| Store Temperature | -10°C~+60°C |
| Store Humidity | 20% - 95% |
| Working Temperature | -10°C~+50°C |
| Working Humidity | 20% - 80% |
| Dimension | φ145.4mmX147mmX154mm |
| Weight | 1.29KG |
| Using Environment | Indoor |

For more information please contact:



BOCK OPTRONICS INC.
14 Steinway Blvd., Unit 7
Toronto, Ontario M9W 6M6
Tel: (416) 674-2804
sales@bockoptronics.ca
www.bockoptronics.ca