

MB-CFL

The MetaBright™ Compact Front Light features eight high powered LEDs, proprietary Metaphase thermal management technology, a built-in constant current driver, and a built-in Strobe with 10X power boosting. The MB-CFL was designed for longer working distances and features a rugged industrial housing such as those found in industrial robotics work envelopes.



FEATURES

- Homogenous light output that provides high intensity illumination
- Shock and vibration resistant
- LED thermal management for stable performance
- Flicker free performance and instant start up with Metaphase analog driver technology
- Built-in Strobe with 10X power boosting
- Built-in Constant Current Driver with 0 – 10VDC intensity control, compatible with DDC-3 and ILD-35 Dimmers

WAVELENGTHS

Order ID	Description / nanometers
W	White (6000K), Nominal
R	Red / 630nm
G	Green / 530nm
B	Blue / 470nm
IR850	Infrared / 850nm
UV365	Ultraviolet Short / 365nm
UV395	Ultraviolet Long / 395nm

GENERAL SPECIFICATIONS

Power Source:	24VDC ±5%
Cable (Standard):	10-foot cable with flying leads
Housing:	Black Anodized Aluminum
Ambient Temp:	-20°C to 40°C
Lifetime Expectancy:	75,000 hours (except UV)

MB-CFL

Compact Front Light							
MODEL	Dimensions W x L x H Inches (cm)	Active Area Inches (cm)	Weight lbs (grams)	Cable QTY	Cable Length	Cable AWG/ Conductors	Max Input Current @24VDC
MB-CFL2.5x1.25	3.4 x 3.9 x 1.0 (8.64 x 9.89 x 2.54)	1.45 x 2.90 (3.68 x 7.37)	.50 (227)	1	10ft	24/4 or 24/6	0.5A

Wiring (4 conductor with Intensity Control)**	
Wire Color	Function
RED	+24VDC
WHITE	0-10VDC INTENSITY CONTROL
BLACK	GROUND (24V RTN)
GREEN	SIGNAL GROUND

Wiring (4 conductor without Intensity Control)	
Wire Color	Function
RED	+24VDC
WHITE	+24VDC
BLACK	GROUND (24V RTN)
GREEN	GROUND (24V RTN)

Wiring (6 conductor with Intensity Control)**	
Wire Color	Function
RED, BROWN	+24VDC
GREEN	SIGNAL GROUND
BLACK, BLUE	GROUND (24V RTN)
WHITE	0-10VDC INTENSITY CONTROL

When not using Intensity Control, connect the 0-10V control line to +24VDC and connect Signal Ground to Ground (24V RTN)

Wiring (6 conductor Strobe mode)	
Wire Color	Function
RED, BROWN	+24VDC
BLACK	GROUND (24V RTN)
WHITE	RISING EDGE TRIGGER
BLUE	FALLING EDGE TRIGGER
GREEN	TRIGGER GROUND

M12 (5 position male)**	
Pin #	Function
1	+24VDC
2	0-10VDC Intensity Control
3	GROUND (24V RTN)
4	SIGNAL GROUND
5	No Connection

The M12 connector option is not recommended for lights rated more than 4 amps

Wiring with ULC-2	
Wire Color	Function
RED, WHITE (+)	LED INPUT
BLACK, GREEN (-)	

Terminated within a 2 position ULC-2 output connector (Phoenix Contact P/N: BCP-508-2)

**Note: The 0-10VDC Intensity Control input can accept voltages from 0-24VDC where the light will operate at full intensity in the 10-24VDC range. The light is proportionally dimmer for any Intensity Control voltage less than 10VDC and the light is OFF at approximately 0V or not connected (floating).

MB-CFL

PART NUMBER KEY											
MODEL	SIZE	-	WAVELENGTH	-	DRIVER* (most common)	-	LENS	-	CABLE LENGTH	-	CONN.** (most Common)
MB-CFL	XXX	-	XXXXXX	-	XXXXXX	-	XXX	-	XXX	-	XXXX
MB-CFL	2.5x1.25		W (White 6000K, Nominal) R (Red 630nm) G (Green 530nm) B (Blue 470nm) IR850 (Infrared 850nm) UV365 (UV Short 365nm) UV395 (UV Long 395nm)		24Z 24-BISXXX 24-ILD 24Z-TRG U¹		L11 (11°) L30 (30°)		5M 10M Length can be customized: ex.7M=7meters Select or leave blank for 3 meters		M12D^{1 2} Select or leave blank for flying leads
Example 1: MB-CFL2.5x1.25-BIS300-L30 Example 2: MB-CFL2.5x1.25-24Z-6M					¹ Not available in lights exceeding 4A input current ² Default cable length for an M12D connector is 19 inches						

Contact Metaphase Technologies or your local representative for options such as custom diffusers, lenses, polarizers, IP-rated enclosures for harsh environments, higher intensity, custom wavelengths, higher uniformity, etc. Not all options are available for all lights.

MB-CFL

Sample Part Number: **MB-CFL2.5x1.25-BIS300-L30**

REVISIONS				
ZONE	REV.	DESCRIPTION	DATE	APPROVED
	B	P/N WAS FL302, KW	12/7/2011	
	C	REVISED / REFORMATTED	7/25/2016	
	D	HOLE CENTERS UPDATED TO REFLECT CURRENT FL301 HOUSING BEING UNIVERSALLY USED	7/6/2017	

Metaphase Technologies, Inc. 211 Sinclair Road, Suite 100, Bristol, PA. 19007 215-639-8699 Fax 215-639-0977			
QUANTITY: Per order	MATERIAL: Per BOM	FINISH: Black Anodize	TREATMENT: N/A
Approval Signature _____		Date / / _____	

TOLERANCE/FINISH UNLESS OTHERWISE SPECIFIED INCHES (MM) (25/75MS) (RA3.2um) X X .XX .XXX (+.03) (-.03) ±.010 ±.005 ANGLES ±1° (+.76) (±.25) (±.13)		THIS DOCUMENT IS THE PROPERTY OF METAPHASE TECHNOLOGIES, INC. WHOM MAY LOAN IT, SUBJECT TO RETURN UPON DEMAND. IT INCLUDES CONFIDENTIAL & PROPRIETARY INFORMATION WHICH MAY NOT BE DISCLOSED TO ANY THIRD PARTY, AND/OR USED FOR ANY PURPOSE CONTRARY TO ITS INTENDED USE, WITHOUT THE EXPRESSED PRIOR WRITTEN CONSENT OF METAPHASE TECHNOLOGIES, INC.	
TITLE: Front Light, High Power Compact USED ON: PER CUSTOMER SIZE: B DRAWING NUMBER: CFL2.5X1.25-01 REV: D SCALE: 1:1 SHEET 1 OF 1			

COMPLIANCE



CONTACT US

For more information please contact:

BOCK OPTRONICS INC.
14 Steinway Blvd., Unit 7
Toronto, Ontario M9W 6M6



Tel: (416) 674-2804
sales@bockoptronics.ca
www.bockoptronics.ca