

AXIS Camera Station S2208 Appliance

All-in-one recorder with PoE switch for UHD surveillance

AXIS Camera Station S2208 Appliance is an all-in-one recording solution with integrated, manageable PoE switch designed to deliver reliable high-definition surveillance with up to 4K resolution. For quick and easy installation, AXIS S2208 is preconfigured and preloaded with AXIS Camera Station video management software, and includes licenses for 8 channels plus all necessary system software. AXIS Camera Station offers an intuitive user interface that allows users to take full advantage of Axis wide range of video surveillance cameras and other IP products. With the operating system stored on a solid-state drive (SSD) and 5-year warranty, AXIS S2208 provides a reliable surveillance solution.

- > [All-in-one solution with integrated PoE switch](#)
- > [High-definition surveillance with up to 4K resolution](#)
- > [AXIS Camera Station licenses included](#)
- > [Full compatibility with Axis products](#)



AXIS Camera Station S2208 Appliance

Licenses	8 AXIS Camera Station core licenses included and tied to the hardware. Can be upgraded with additional licenses (sold separately).	Up to 8 cameras split view Supports two monitors, maximum one 4K monitor recommended Playback: Supports the same split scenarios as live view Supports only one monitor
System scalability	Qualified for up to 8 video channels and 16 doors	
Hardware		
Processor	Intel® Core™ i3	
Memory	8 GB	
Storage	Surveillance Class HDD Total HDD slot: 2 Free HDD slot: 1 Out-of-the-box storage: 4 TB (1x4 TB)	
Switch	8 ports integrated, 135 W total power budget Power over Ethernet (PoE) IEEE 802.3at Class 4	
Graphic card	Intel® HD Graphics	
Power	Max 270 W, 135 W PoE dedicated 100 – 240 V AC, 3.5 A, 50/60 Hz 54 V DC, 5 A External power adapter	
Connectors	Front side: 1x USB 3.0 1x Audio line in 1x Audio line out Rear side Switch: 8x PoE ports 10/100 Mbps 1x SFP 10/100/1000 Mbps 1x RJ45 10/100/1000 Mbps Rear side Server: 1x RJ45 10/100/1000 Mbps 2x USB 2.0 1 Displayport™ 1 HDMI port	
Video		
Video streaming	Live view: 1 x 4K stream full screen 4 split x 1080p	
Recording	Qualified for recording up to 8 video channels with a total recording rate up to 192 Mbit per second	
General		
Operating system	Microsoft® Windows® 10 IoT Enterprise SAC Operating system recovery: yes Operating system drive: 120 GB SSD	
Operating conditions	0 °C to 40 °C (32 °F to 104 °F) Humidity: 10–90% RH (non-condensing)	
Storage conditions	–40 °C to 65 °C (–40 °F to 149 °F)	
Approvals	EMC CNS 13438, EAC, EN 55024, EN 55032 Class A, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, KC KN32 Class A, KC KN35, RCM AS/NZS CISPR 32 Class A, VCCI Class A Safety IEC/EN 60950-1, IEC/EN 62368-1, KC-Mark, UL 62368-1, IS 13252	
Dimensions	330 x 230 x 78 mm (13 x 9.1 x 3.1 in)	
Weight	5.8 kg (12.8 lb)	
Included accessories	Rack ears, power adapter	
Optional accessories	Surveillance Hard Drive 4 TB available from Axis AXIS TS2901 Appliance Stand Axis desktop terminals Axis Ethernet surge protector For more accessories, see axis.com	
Warranty	Recorder and hard drive: 5-year warranty, see axis.com/warranty	

AXIS Camera Station

For details about AXIS Camera Station features and functions, see the AXIS Camera Station datasheet on axis.com

Environmental responsibility:
axis.com/environmental-responsibility

For more information please contact:



BOCK OPTRONICS INC.
14 Steinway Blvd., Unit 7
Toronto, Ontario M9W 6M6

Tel: (416) 674-2804
sales@bockoptronics.ca
www.bockoptronics.ca

AXIS Camera Station S2212 Appliance

All-in-one recorder with PoE switch for UHD surveillance

AXIS Camera Station S2212 Appliance is an all-in-one recording solution with integrated, manageable PoE switch designed to deliver reliable high-definition surveillance with up to 4K resolution. For quick and easy installation, AXIS S2212 is preconfigured and preloaded with AXIS Camera Station video management software, and includes licenses for 12 channels plus all necessary system software. AXIS Camera Station offers an intuitive user interface that allows users to take full advantage of Axis wide range of video surveillance cameras and other IP products. With the operating system stored on a solid-state drive (SSD) and 5-year warranty, AXIS S2212 provides a reliable surveillance solution.

- > [All-in-one solution with integrated PoE switch](#)
- > [High-definition surveillance with up to 4K resolution](#)
- > [AXIS Camera Station licenses included](#)
- > [Full compatibility with Axis products](#)



AXIS Camera Station S2212 Appliance

Licenses	12 AXIS Camera Station core licenses included and tied to the hardware. Can be upgraded with additional licenses (sold separately).	Up to 12 cameras split view Supports two monitors, maximum one 4K monitor recommended Playback: Supports the same split scenarios as live view Supports only one monitor
System scalability	Qualified for up to 12 video channels and 24 doors	
Hardware		
Processor	Intel® Core™ i3	
Memory	8 GB	
Storage	Surveillance Class HDD Total HDD slot: 2 Free HDD slot: 1 Out-of-the-box storage: 6 TB (1x6 TB)	
Switch	12 ports integrated, 135 W total power budget Power over Ethernet (PoE) IEEE 802.3at Class 4	
Graphic card	Intel® HD Graphics	
Power	Max 270 W, 135 W PoE dedicated 100 – 240 V AC, 3.5 A, 50/60 Hz 54 V DC, 5 A External power adapter	
Connectors	Front side: 1x USB 3.0 1x Audio line in 1x Audio line out Rear side Switch: 12x PoE ports 10/100 Mbps 1x SFP 10/100/1000 Mbps 1x RJ45 10/100/1000 Mbps Rear side Server: 1x RJ45 10/100/1000 Mbps 2x USB 2.0 1 Displayport™ 1 HDMI port	
Video		
Video streaming	Live view: 1 x 4K stream full screen 4 split x 1080p	
Recording	Qualified for recording up to 12 video channels with a total recording rate up to 192 Mbit per second	
General		
Operating system	Microsoft® Windows® 10 IoT Enterprise SAC Operating system recovery: yes Operating system drive: 120 GB SSD	
Operating conditions	0 °C to 40 °C (32 °F to 104 °F) Humidity: 10–90% RH (non-condensing)	
Storage conditions	–40 °C to 65 °C (–40 °F to 149 °F)	
Approvals	EMC CNS 13438, EAC, EN 55024, EN 55032 Class A, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, KC KN32 Class A, KC KN35, RCM AS/NZS CISPR 32 Class A, VCCI Class A Safety IEC/EN 60950-1, IEC/EN 62368-1, KC-Mark, UL 62368-1, IS 13252	
Dimensions	330 x 230 x 78 mm (13 x 9.1 x 3.1 in)	
Weight	5.8 kg (12.8 lb)	
Included accessories	Rack ears, power adapter	
Optional accessories	Surveillance Hard Drive 6 TB available from Axis AXIS TS2901 Appliance Stand Axis desktop terminals Axis Ethernet surge protector For more accessories, see axis.com	
Warranty	Recorder and hard drive: 5-year warranty, see axis.com/warranty	

AXIS Camera Station

For details about AXIS Camera Station features and functions, see the AXIS Camera Station datasheet on axis.com

Environmental responsibility:
axis.com/environmental-responsibility

For more information please contact:



BOCK OPTRONICS INC.

14 Steinway Blvd., Unit 7
Toronto, Ontario M9W 6M6

Tel: (416) 674-2804
sales@bockoptronics.ca
www.bockoptronics.ca

AXIS Camera Station S1116 MT Recorder

Out-of-the box ready server and client for UHD surveillance

AXIS Camera Station S1116 Recorder is an out-of-the-box ready workstation validated for reliable high-definition surveillance up to 4K. For quick and easy installation, AXIS S1116 is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 16 channels plus all necessary system software. The system configuration can easily be imported from AXIS Site Designer, and AXIS Camera Station lets users take full advantage of Axis wide range of video surveillance devices. With enterprise-grade hard disks, operating system stored on solid-state drive (SSD), and expandable storage capacity, AXIS S1116 provides high-performance and reliability for your system.

- > [Ease of installation](#)
- > [AXIS Camera Station licenses included](#)
- > [Full compatibility with Axis products](#)
- > [5-year warranty](#)



AXIS Camera Station S1116 MT Recorder

Licenses	16 AXIS Camera Station core licenses included and tied to the hardware. Can be upgraded with additional licenses (sold separately).	Playback: 4 x 1080p camera split views or 1 x 4K camera view Supports two monitors.
System scalability	Qualified for up to 32 video channels and 64 doors	Recording Qualified for recording up to 32 video channels with a total recording rate up to 256 Mbit per second.
Hardware		General
Processor	Intel® Core™ i5	Operating system Microsoft® Windows® 10 IoT Enterprise SAC Built-in operating system recovery: yes Operating system drive: 128 GB SSD
Memory	8 GB	Operating conditions 0 °C to 45 °C (32 °F to 113 °F)
Storage	Enterprise Class HDD Total HDD slot: 2 Free HDD slot: 1 Out-of-the-box storage: 8 TB (1x8 TB)	Storage conditions -40 °C to 65 °C (-40 °F to 149 °F)
RAID	RAID levels: 0, 1	Approvals EMC EN 55032, EN 55024, EN/IEC 61000-3-2, EN/IEC 61000-3-3, EN 50564, EN 62623, FCC Part 15 Subpart B Class B, ICES-003 Class B, VCCI Class B, RCM AS/NZS CISPR 32 Class B, KC KN32 Class B, KN35, Safety IEC/EN/UL 60950-1, EN 62368-1, NOM, BSMI, EAC
Graphic card	Intel® HD Graphics	Dimensions 274 x 154 x 350 mm (10.8 x 6.1 x 13.8 in)
Power	360 W (100 - 240 V AC, 50/60 Hz, 5.0 - 2.5 A)	Weight 7.4 kg (16 lb)
Connectors	Front side: 1x Universal audio jack 2x USB 2.0 1x USB 3.1 1x USB 3.1 Type-C Rear side: 2x USB 2.0 4x USB 3.1 2x DisplayPort™ 1.2 1x Ethernet (RJ45) 1 GbE 1x Audio line out 1x Serial port	Included accessories Power cord, keyboard, mouse
Video		Optional accessories Axis joysticks and control boards For more accessories, see axis.com
Video streaming	Live view: Up to 25 camera split views or 1 x 4K camera view	Warranty 5-year warranty, see axis.com/warranty

AXIS Camera Station

For details about AXIS Camera Station features and functions, see the AXIS Camera Station datasheet on axis.com

Environmental responsibility:
axis.com/environmental-responsibility

For more information please contact:



BOCK OPTRONICS INC.
14 Steinway Blvd., Unit 7
Toronto, Ontario M9W 6M6

Tel: (416) 674-2804
sales@bockoptronics.ca
www.bockoptronics.ca

AXIS Camera Station S1132 Recorder

Out-of-the box ready server for UHD surveillance

AXIS Camera Station S1132 Recorder is an out-of-the-box ready rack server validated for reliable ultra high-definition recording. For quick and easy installation, AXIS S1132 is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 32 channels plus all necessary software. The system configuration can easily be imported from AXIS Site Designer, and AXIS Camera Station lets users take full advantage of Axis wide range of video surveillance devices. With redundant enterprise-grade hard disks and power supplies, operating system stored on solid-state drive (SSD), AXIS S1132 provides high-performance and reliability for your system.

- > [Ease of installation](#)
- > [AXIS Camera Station licenses included](#)
- > [Full compatibility with Axis products](#)
- > [5-year warranty](#)



AXIS Camera Station S1132 Recorder

Licenses	32 AXIS Camera Station core licenses included and tied to the hardware. Can be upgraded with additional licenses (sold separately).	Recording	Qualified for recording up to 48 video channels with a total recording rate up to 384 Mbit per second.
System scalability	Qualified for up to 48 video channels and 96 doors	General	
Hardware		Operating system	Microsoft® Windows® 10 IoT Enterprise SAC Built-in operating system recovery: yes Operating system drive: 240 GB SSD
Processor	Intel® Core™ i3	Operating conditions	10 °C to 35 °C (50 °F to 95 °F) Humidity 20–80% RH (non-condensing)
Memory	8 GB	Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F)
Storage	Hot swappable Enterprise Class HDD Total HDD slot: 4 Free HDD slot: 0 Out-of-the-box storage: 12 TB after RAID 5 Out-of-the-box capacity without RAID: 16 TB (4x4 TB)	Approvals	EMC EN 55032 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3, FCC Part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), RCM AS/NZS CISPR 32 Class A, VCCI Class A, KC KN 32 Class A, KC KN 35 Safety IEC/EN/UL 60950-1, EN 62368-1, NOM, BSMI, EAC
RAID	Factory RAID level: 5 RAID levels: 0, 1, 5, 6, 10	Dimensions	596 x 484 x 43 mm (23.47 x 19.06 x 1.7 in), 1U chassis
Power	2 x 350 W hot-plug redundant power supplies (included) (100 - 240 V AC, 50/60 Hz, 4.8 - 2.4 A)	Weight	13.5 kg (29.7 lb)
Connectors	Front side: 1x USB 2.0 Rear side: 2x USB 2.0 2x Ethernet (RJ45) 1 GbE 1x VGA 1x Serial port	Included accessories	Rack rails, 2x C13 to C14 power cords for rack PDU (Wall plug power cords are not included)
Video		Optional accessories	Axis desktop terminals For more accessories, see axis.com
Video streaming	Not intended for local viewing of video. Recommended to use AXIS desktop terminals.	Warranty	5-year warranty, see axis.com/warranty

AXIS Camera Station

For details about AXIS Camera Station features and functions, see the AXIS Camera Station datasheet on axis.com

Environmental responsibility:
axis.com/environmental-responsibility

For more information please contact:



BOCK OPTRONICS INC.
14 Steinway Blvd., Unit 7
Toronto, Ontario M9W 6M6

Tel: (416) 674-2804
sales@bockoptronics.ca
www.bockoptronics.ca

AXIS S3008 Recorder

Compact recorder with integrated switch for UHD surveillance

AXIS S3008 Recorder is a compact recorder with an integrated PoE switch for up to 8 cameras. It provides reliable recording thanks to the surveillance-grade hard drive. This high-performance recorder offers gigabit uplink for video recordings in ultra-high definition and includes a 5-year warranty. The recorder is supported by the AXIS Companion video management software and mobile app.

- > [Compact recorder with integrated PoE switch](#)
- > [Easy to install and operate](#)
- > [Surveillance-grade hard drive](#)
- > [USB port for exporting video](#)
- > [5-year warranty](#)



AXIS S3008 Recorder

Models	AXIS S3008 Recorder 2 TB AXIS S3008 Recorder 4 TB AXIS S3008 Recorder 8 TB	Total PoE power budget: 2 TB and 4 TB: 65 W 8 TB: 60 W PoE-class reservation and allocation of Max-power via LLDP for supported devices
Storage	Surveillance class HDD: 2 TB, 4 TB or 8 TB	
System on chip (SoC)		
Model	i.MX 8QuadPlus	
Video		
Recording	Qualified for recording up to 8 video sources with a total recording rate up to 160 Mbit per second	
Video compression	H.264 (MPEG-4 Part 10/AVC), H.265 (MPEG-H Part 2/HEVC) Depending on camera support	
Resolution	Supports all camera resolutions	
Frame rate	Supports all camera frame rates	
Audio streaming	One-way audio recording depending on camera support	
Audio encoding	AAC Depending on camera support	
Network		
Network function	NTP server	
Security	Hard drive encryption (AES-XTS-Plain64 256bit), password protection, digest authentication, user access log, centralized certificate management, signed firmware, secure boot, IEEE 802.1x (EAP-TLS) network access control, Axis Edge Vault with Axis device ID	
Supported protocols	IPv4, IPv6 USGv6, ICMPv4/ICMPv6, HTTP, HTTPS, HTTP/2, TLS, QoS, SFTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP™, DNS/DNSv6, NTP, TCP, UDP, IGMP, ICMP, DHCPv4/v6, ARP, SSH	
System integration		
Application Programming Interface	One-click cloud connection	
Events & alarms		
Event triggers	Hard drive error, hard drive temperature warning, CPU temperature warning, fan error, PoE budget exceeded MQTT subscribe	
General		
Supported devices	Axis network cameras and encoders with firmware 5.50 or later, AXIS Companion mini cameras are not supported	
Input	Power supply: 50–60 Hz, 100–240 V AC, max 90 W Recorder: 1.88 A, 48 V DC, max 90 W	
Output	Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 0, Class 1, Class 2, and Class 3	
Casing	Aluminum and plastic casing Color: Black	
Operating conditions	0 °C to 45 °C (32 °F to 113 °F) Humidity 10–85% RH (non-condensing)	
Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 5–95% RH	
Connectors	Rear side: 8x RJ45 10BASE-T/100BASE-TX PoE 1x RJ45 10BASE-T/100BASE-TX/1000BASE-T DC input Side: 1x USB 3.0	
Approvals	EMC: EAC, EN 55024, EN 55032 Class A, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), KC KN32 Class A, KC KN35, RCM AS/NZS CISPR 32 Class A, VCCI Class A Safety: IEC/EN 62368-1, UL 62368-1, IS 13252 Environment: IEC 60068-2-1, IEC 60068-2-14, IEC 60068-2-2, IEC 60068-2-27, IEC 60068-2-6, IEC 60068-2-78, IEC/EN 60529 IP3X	
Sustainability	PVC free	
Dimensions	180 x 180 x 53 mm (7 1/16 x 7 1/16 x 2 1/16 in)	
Weight	2 TB: 1310 g (2.9 lb) 4 TB: 1350 g (3.0 lb) 8 TB: 1450 g (3.2 lb)	
Included accessories	AXIS Mains adapter 48V DC 90W (01508-001), installation guide	
Optional accessories	AXIS TS3001 Recorder Mount	
Video management software	AXIS Companion version 4 available at axis.com/vms	
Warranty	Recorder and hard drive: 5-year warranty, see axis.com/warranty	

Environmental responsibility:
axis.com/environmental-responsibility

For more information please contact:



BOCK OPTRONICS INC.
14 Steinway Blvd., Unit 7
Toronto, Ontario M9W 6M6

Tel: (416) 674-2804
sales@bockoptronics.ca
www.bockoptronics.ca

AXIS Camera Station S2216 Appliance

All-in-one recorder with PoE switch for UHD surveillance

AXIS Camera Station S2216 Appliance is an all-in-one recording solution with integrated, manageable PoE switch designed to deliver reliable high-definition surveillance with up to 4K resolution. For quick and easy installation, AXIS S2216 is preconfigured and preloaded with AXIS Camera Station video management software, and includes licenses for 16 channels plus all necessary system software. AXIS Camera Station offers an intuitive user interface that allows users to take full advantage of Axis wide range of video surveillance cameras and other IP products. With the operating system stored on a solid-state drive (SSD) and 5-year warranty, AXIS S2216 provides a reliable surveillance solution.

- > [All-in-one solution with integrated PoE switch](#)
- > [High-definition surveillance with up to 4K resolution](#)
- > [AXIS Camera Station licenses included](#)
- > [Full compatibility with Axis products](#)



AXIS Camera Station S2216 Appliance

Licenses	16 AXIS Camera Station core licenses included and tied to the hardware. Can be upgraded with additional licenses (sold separately).	4 split x 1080p Up to 16 cameras split view Supports two monitors, maximum one 4K monitor recommended Playback: Supports the same split scenarios as live view Supports only one monitor
System scalability	Qualified for up to 16 video channels and 32 doors	
Hardware		
Processor	Intel® Core™ i5	
Memory	8 GB	
Storage	Surveillance Class HDD Total HDD slot: 4 Free HDD slot: 2 Out-of-the-box storage: 8 TB (2x4 TB)	
RAID	RAID levels: 0, 1, 10	
Switch	16 ports integrated, 260 W total power budget Power over Ethernet (PoE) IEEE 802.3at Class 4	
Graphic card	Intel® HD Graphics	
Power	Max 520 W, 260 W PoE dedicated 100 - 240 V AC, 6.5-2.5 A, 50/60 Hz	
Connectors	Front side: 1x USB 3.0 1x Audio line in 1x Audio line out Rear side Switch: 16x PoE ports 10/100 Mbps 1x SFP 10/100/1000 Mbps 1x RJ45 10/100/1000 Mbps Rear side Server: 1x RJ45 10/100/1000 Mbps 2x USB 2.0 1 Displayport™ 1 HDMI port	
Video		
Video streaming	Live view: 1 x 4K stream full screen	
Recording	Qualified for recording up to 16 video channels with a total recording rate up to 384 Mbit per second	
General		
Operating system	Microsoft® Windows® 10 IoT Enterprise SAC Operating system recovery: yes Operating system drive: 120 GB SSD	
Operating conditions	0 °C to 40 °C (32 °F to 104 °F) Humidity: 10-90% RH (non-condensing)	
Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F)	
Approvals	EMC CNS 13438, EAC, EN 55024, EN 55032 Class A, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, KC KN32 Class A, KC KN35, RCM AS/NZS CISPR 32 Class A, VCCI Class A Safety IEC/EN 60950-1, IEC/EN 62368-1, KC-Mark, UL 62368-1, IS 13252	
Dimensions	476 x 440 x 45 mm (18.7 x 17.3 x 1.8 in), 1U chassis	
Weight	11 kg (24.3 lb)	
Included accessories	Rack rails, power cord	
Optional accessories	Surveillance Hard Drive 4 TB available from Axis Axis desktop terminals Axis Ethernet surge protector For more accessories, see axis.com	
Warranty	Recorder and hard drive: 5-year warranty, see axis.com/warranty	

AXIS Camera Station

For details about AXIS Camera Station features and functions, see the AXIS Camera Station datasheet on axis.com

Environmental responsibility:
axis.com/environmental-responsibility

For more information please contact:



BOCK OPTRONICS INC.
14 Steinway Blvd., Unit 7
Toronto, Ontario M9W 6M6

Tel: (416) 674-2804
sales@bockoptronics.ca
www.bockoptronics.ca

AXIS Camera Station S2216 Appliance

All-in-one recorder with PoE switch for UHD surveillance

AXIS Camera Station S2216 Appliance is an all-in-one recording solution with integrated, manageable PoE switch designed to deliver reliable high-definition surveillance with up to 4K resolution. For quick and easy installation, AXIS S2216 is preconfigured and preloaded with AXIS Camera Station video management software, and includes licenses for 16 channels plus all necessary system software. AXIS Camera Station offers an intuitive user interface that allows users to take full advantage of Axis wide range of video surveillance cameras and other IP products. With the operating system stored on a solid-state drive (SSD) and 5-year warranty, AXIS S2216 provides a reliable surveillance solution.

- > [All-in-one solution with integrated PoE switch](#)
- > [High-definition surveillance with up to 4K resolution](#)
- > [AXIS Camera Station licenses included](#)
- > [Full compatibility with Axis products](#)



AXIS Camera Station S2216 Appliance

Licenses	16 AXIS Camera Station core licenses included and tied to the hardware. Can be upgraded with additional licenses (sold separately).	4 split x 1080p Up to 16 cameras split view Supports two monitors, maximum one 4K monitor recommended Playback: Supports the same split scenarios as live view Supports only one monitor
System scalability	Qualified for up to 16 video channels and 32 doors	
Hardware		
Processor	Intel® Core™ i5	
Memory	8 GB	
Storage	Surveillance Class HDD Total HDD slot: 4 Free HDD slot: 2 Out-of-the-box storage: 8 TB (2x4 TB)	
RAID	RAID levels: 0, 1, 10	
Switch	16 ports integrated, 260 W total power budget Power over Ethernet (PoE) IEEE 802.3at Class 4	
Graphic card	Intel® HD Graphics	
Power	Max 520 W, 260 W PoE dedicated 100 - 240 V AC, 6.5-2.5 A, 50/60 Hz	
Connectors	Front side: 1x USB 3.0 1x Audio line in 1x Audio line out Rear side Switch: 16x PoE ports 10/100 Mbps 1x SFP 10/100/1000 Mbps 1x RJ45 10/100/1000 Mbps Rear side Server: 1x RJ45 10/100/1000 Mbps 2x USB 2.0 1 Displayport™ 1 HDMI port	
Video		
Video streaming	Live view: 1 x 4K stream full screen	
Recording	Qualified for recording up to 16 video channels with a total recording rate up to 384 Mbit per second	
General		
Operating system	Microsoft® Windows® 10 IoT Enterprise SAC Operating system recovery: yes Operating system drive: 120 GB SSD	
Operating conditions	0 °C to 40 °C (32 °F to 104 °F) Humidity: 10-90% RH (non-condensing)	
Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F)	
Approvals	EMC CNS 13438, EAC, EN 55024, EN 55032 Class A, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, KC KN32 Class A, KC KN35, RCM AS/NZS CISPR 32 Class A, VCCI Class A Safety IEC/EN 60950-1, IEC/EN 62368-1, KC-Mark, UL 62368-1, IS 13252	
Dimensions	476 x 440 x 45 mm (18.7 x 17.3 x 1.8 in), 1U chassis	
Weight	11 kg (24.3 lb)	
Included accessories	Rack rails, power cord	
Optional accessories	Surveillance Hard Drive 4 TB available from Axis Axis desktop terminals Axis Ethernet surge protector For more accessories, see axis.com	
Warranty	Recorder and hard drive: 5-year warranty, see axis.com/warranty	

AXIS Camera Station

For details about AXIS Camera Station features and functions, see the AXIS Camera Station datasheet on axis.com

Environmental responsibility:
axis.com/environmental-responsibility

For more information please contact:



BOCK OPTRONICS INC.
14 Steinway Blvd., Unit 7
Toronto, Ontario M9W 6M6

Tel: (416) 674-2804
sales@bockoptronics.ca
www.bockoptronics.ca

AXIS Camera Station S1132 Tower Recorder

Out-of-the-box ready server and client for UHD surveillance

AXIS Camera Station S1132 Tower Recorder is an out-of-the-box ready-to-use server and client in tower form factor, validated for reliable ultra-high-definition recording and monitoring. It comes preconfigured and preloaded with AXIS Camera Station including licenses for 32 channels, as well as all the necessary software. The system configuration can be imported from AXIS Site Designer and AXIS Camera Station lets users take advantage of the wide range of Axis video surveillance devices. With redundant enterprise-grade hard drives and power supplies, operating system stored on solid-state drive (SSD) and built-in operating system recovery, AXIS S1132 Tower provides high-performance and reliability for your system.

- > [Flexible storage options including RAID](#)
- > [Optimized for Axis network products](#)
- > [Quick system setup and intuitive operation](#)
- > [Validated with extensive support](#)
- > [AXIS Camera Station licenses included](#)



AXIS Camera Station S1132 Tower Recorder

Models	AXIS S1132 Tower 32 TB AXIS S1132 Tower 64 TB	Video streaming	Live view: 1 stream x 4K at 30 fps 4 split x 1080p at 30 fps 9 split x 720p at 15 fps 24 split x 360p at 15 fps Any combination of the above for maximum two 4K monitors Playback: Supports one monitor with the same split scenarios as for live view.
Licenses	32 AXIS Camera Station core licenses included and tied to the hardware. Can be upgraded with additional licenses (sold separately).	Recording	Qualified for recording up to 48 video channels with a total recording rate up to 384 Mbit per second.
System scalability	Qualified for up to 48 video channels and 96 doors	General	
Hardware			
Processor	Intel® Core™ i3	Operating system	Microsoft® Windows® 10 IoT Enterprise SAC Built-in operating system recovery: yes Operating system drive: SSD
Memory	16 GB (2x8 GB)	Operating conditions	10 °C to 35 °C (50 °F to 95 °F) Humidity 10–80% RH (non-condensing)
Storage	S1132 Tower 32 TB Hot swappable Enterprise Class HDD Total HDD slot: 8 Free HDD slot: 4 Out-of-the-box storage: 24 TB after RAID 5 Out-of-the-box capacity without RAID: 32 TB (4x8 TB) S1132 Tower 64 TB Hot swappable Enterprise Class HDD Total HDD slot: 8 Free HDD slot: 0 Out-of-the-box storage: 56 TB after RAID 5 Out-of-the-box capacity without RAID: 64 TB (8x8 TB)	Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 5–95% RH (non-condensing)
RAID	Factory RAID level: 5 RAID levels: 0, 1, 5, 6, 10, JBOD	Approvals	EMC EN 55032 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3, FCC Part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), RCM AS/NZS CISPR 32 Class A, VCCI Class A, KC KN 32 Class A, KC KN 35 Safety IEC/EN/UL 60950-1, EN 62368-1, NOM, BSMI, EAC
Graphic card	Nvidia® Quadro®	Dimensions	218 x 603 x 430 mm (8.59 x 23.75 x 16.93 in)
Power	2 x 495 W hot-plug redundant power supplies (included) (100 – 240 V AC, 50/60 Hz, 6.5 – 3.0 A)	Weight	S1132 32 TB 22.9 kg (50.5 lb) S1132 64 TB 26.5 kg (58.4 lb)
Connectors	Front side: 1x USB 3.1 Rear side: 2x USB 3.1 4x USB 2.0 2x Ethernet (RJ45) 1 GbE 3x Mini DisplayPort™ (max two monitors recommended)	Included accessories	2x C13 wall plug power cord, 2x Mini DisplayPort™ to DisplayPort™ adapter
Video		Optional accessories	Axis joysticks and control boards For more accessories, see axis.com
		Warranty	5-year warranty, see axis.com/warranty

AXIS Camera Station

For details about AXIS Camera Station features and functions, see the AXIS Camera Station datasheet on axis.com

Environmental responsibility:
axis.com/environmental-responsibility

For more information please contact:



BOCK OPTRONICS INC.
14 Steinway Blvd., Unit 7
Toronto, Ontario M9W 6M6

Tel: (416) 674-2804
sales@bockoptronics.ca
www.bockoptronics.ca

AXIS Camera Station S1116 Racked Recorder

Out-of-the box ready rack server for UHD surveillance

AXIS Camera Station S1116 Recorder is an out-of-the-box ready rack server validated for reliable high-definition surveillance up to 4K. For quick and easy installation, AXIS S1116 is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 16 channels plus all necessary system software. The system configuration can easily be imported from AXIS Site Designer, and AXIS Camera Station lets users take full advantage of Axis wide range of video surveillance devices. With enterprise-grade hard disks, operating system stored on solid-state drive (SSD), and expandable storage capacity, AXIS S1116 provides high-performance and reliability for your system.

- > [Ease of installation](#)
- > [AXIS Camera Station licenses included](#)
- > [Full compatibility with Axis products](#)
- > [5-year warranty](#)



AXIS Camera Station S1116 Racked Recorder

Licenses	16 AXIS Camera Station core licenses included and tied to the hardware. Can be upgraded with additional licenses (sold separately).	General	
System scalability	Qualified for up to 32 video channels and 64 doors	Operating system	Microsoft® Windows® 10 IoT Enterprise SAC Built-in operating system recovery: yes Operating system drive: 256 GB SSD
Hardware		Operating conditions	10 °C to 35 °C (50 °F to 95 °F) Humidity 10–85% RH (non-condensing)
Processor	Intel® Core™ i5	Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F)
Memory	8 GB	Approvals	EMC EN 55032 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3, FCC Part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), RCM AS/NZS CISPR 32 Class A, VCCI Class A, KC KN 32 Class A, KC KN 35 Safety IEC/EN/UL 60950-1, EN 62368-1, NOM, BSMI, EAC
Storage	Enterprise Class HDD Total HDD slot: 3 Free HDD slot: 2 Out-of-the-box storage: 8 TB (1x8 TB)	Dimensions	589 x 482 x 43 mm (23.2 x 19 x 1.7 in)
RAID	RAID levels: 0, 1	Weight	9.6 kg (21 lb)
Power	550 W (100 - 240 V AC, 50/60 Hz, 7.4 - 3.7 A)	Included accessories	Rack rails, 1x USB-C to VGA adapter, 1x C13 to C14 power cord for rack PDU (Wall plug power cord is not included)
Connectors	Front side: 2x USB 3.1 1x USB 3.1 Type-C 1x Universal audio jack 1x SD card reader Rear side: 2x USB 3.1 Type-C / DisplayPort™ 2x Ethernet (RJ45): 1x 1 GbE / 1x 10 GbE 1x Serial port	Optional accessories	Axis desktop terminals For more accessories, see axis.com
Video		Warranty	5-year warranty, see axis.com/warranty
Video streaming	Not intended for local viewing of video. Recommended to use Axis desktop terminals.		
Recording	Qualified for recording up to 32 video channels with a total recording rate up to 256 Mbit per second.		

AXIS Camera Station

For details about AXIS Camera Station features and functions, see the AXIS Camera Station datasheet on axis.com

Environmental responsibility:
axis.com/environmental-responsibility

For more information please contact:



BOCK OPTRONICS INC.
14 Steinway Blvd., Unit 7
Toronto, Ontario M9W 6M6

Tel: (416) 674-2804
sales@bockoptronics.ca
www.bockoptronics.ca

AXIS Camera Station S2224 Appliance

All-in-one recorder with PoE switch for UHD surveillance

AXIS Camera Station S2224 Appliance is an all-in-one recording solution with integrated, manageable PoE switch designed to deliver reliable high-definition surveillance with up to 4K resolution. For quick and easy installation, AXIS S2224 is preconfigured and preloaded with AXIS Camera Station video management software, and includes licenses for 24 channels plus all necessary system software. AXIS Camera Station offers an intuitive user interface that allows users to take full advantage of Axis wide range of video surveillance cameras and other IP products. With the operating system stored on a solid-state drive (SSD) and 5-year warranty, AXIS S2224 provides a reliable surveillance solution.

- > [All-in-one solution with integrated PoE switch](#)
- > [High-definition surveillance with up to 4K resolution](#)
- > [AXIS Camera Station licenses included](#)
- > [Full compatibility with Axis products](#)



AXIS Camera Station S2224 Appliance

Licenses	24 AXIS Camera Station core licenses included and tied to the hardware. Can be upgraded with additional licenses (sold separately).	4 split x 1080p Up to 24 cameras split view Supports two monitors, maximum one 4K monitor recommended Playback: Supports the same split scenarios as live view Supports only one monitor
System scalability	Qualified for up to 24 video channels and 48 doors	
Hardware		
Processor	Intel® Core™ i5	
Memory	8 GB	
Storage	Surveillance Class HDD Total HDD slot: 4 Free HDD slot: 2 Out-of-the-box storage: 12 TB (2x6 TB)	
RAID	RAID levels: 0, 1, 10	
Switch	24 ports integrated, 260 W total power budget Power over Ethernet (PoE) IEEE 802.3at Class 4	
Graphic card	Intel® HD Graphics	
Power	Max 520 W, 260 W PoE dedicated 100 - 240 V AC, 6.5-2.5 A, 50/60 Hz	
Connectors	Front side: 1x USB 3.0 1x Audio line in 1x Audio line out Rear side Switch: 24x PoE ports 10/100 Mbps 1x SFP 10/100/1000 Mbps 1x RJ45 10/100/1000 Mbps Rear side Server: 1x RJ45 10/100/1000 Mbps 2x USB 2.0 1 Displayport™ 1 HDMI port	
Video		
Video streaming	Live view: 1 x 4K stream full screen	
Recording	Qualified for recording up to 24 video channels with a total recording rate up to 384 Mbit per second	
General		
Operating system	Microsoft® Windows® 10 IoT Enterprise SAC Operating system recovery: yes Operating system drive: 120 GB SSD	
Operating conditions	0 °C to 40 °C (32 °F to 104 °F) Humidity: 10-90% RH (non-condensing)	
Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F)	
Approvals	EMC CNS 13438, EAC, EN 55024, EN 55032 Class A, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, KC KN32 Class A, KC KN35, RCM AS/NZS CISPR 32 Class A, VCCI Class A Safety IEC/EN 60950-1, IEC/EN 62368-1, KC-Mark, UL 62368-1, IS 13252	
Dimensions	476 x 440 x 45 mm (18.7 x 17.3 x 1.8 in), 1U chassis	
Weight	11 kg (24.3 lb)	
Included accessories	Rack rails, power cord	
Optional accessories	Surveillance Hard Drive 6 TB available from Axis Axis desktop terminals Axis Ethernet surge protector For more accessories, see axis.com	
Warranty	Recorder and hard drive: 5-year warranty, see axis.com/warranty	

AXIS Camera Station

For details about AXIS Camera Station features and functions, see the AXIS Camera Station datasheet on axis.com

Environmental responsibility:
axis.com/environmental-responsibility

For more information please contact:



BOCK OPTRONICS INC.
14 Steinway Blvd., Unit 7
Toronto, Ontario M9W 6M6

Tel: (416) 674-2804
sales@bockoptronics.ca
www.bockoptronics.ca

AXIS Camera Station S1148 Recorder

Out-of-the box ready server for UHD surveillance

AXIS Camera Station S1148 Recorder is an out-of-the-box ready rack server validated for reliable ultra high-definition recording. For quick and easy installation, AXIS S1148 is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 48 channels plus all necessary software. The system configuration can easily be imported from AXIS Site Designer, and AXIS Camera Station lets users take full advantage of Axis wide portfolio of video surveillance devices. With redundant enterprise-grade hard disks and power supplies, operating system stored on solid-state drive (SSD), and expandable storage, AXIS S1148 provides high-performance and reliability for your system.

- > **Ease of installation**
- > **AXIS Camera Station licenses included**
- > **Full compatibility with Axis products**
- > **Available with 24TB/ 64TB/ 144TB storage**
- > **5-year warranty**



AXIS Camera Station S1148 Recorder

Models	S1148 24 TB S1148 64 TB S1148 140 TB	2 x 750 W hot-plug redundant power supplies (included) (100-240 V AC, 10 - 5 A, 50/60 Hz)
Licenses	48 AXIS Camera Station core licenses included and tied to the hardware. Can be upgraded with additional licenses (sold separately).	Connectors
System scalability	Qualified for up to 64 video channels and 128 doors	Front side: 1x USB 3.1 Type-C 2x USB 2.0 1x VGA Rear side: 2x USB 3.1 2x Ethernet (RJ45) 1 GbE 1x VGA 1x Serial port
Hardware		
Processor	Intel® Xeon® Silver	Video
Memory	S1148 24 TB 8 GB S1148 64 TB 16 GB S1148 140 TB 32 GB	Video streaming
Storage	S1148 24 TB Hot swappable Enterprise Class HDD Total HDD slot: 8 Free HDD slot: 2 Out-of-the-box storage: 20 TB after RAID 5 Out-of-the-box capacity without RAID: 24 TB (6x4 TB) S1148 64 TB Hot swappable Enterprise Class HDD Total HDD slot: 12 Free HDD slot: 4 Out-of-the-box storage: 56 TB after RAID 5 Out-of-the-box capacity without RAID: 64 TB (8x8 TB) S1148 140 TB Hot swappable Enterprise Class HDD Total HDD slot: 12 Free HDD slot: 0 Out-of-the-box storage: 120 TB after RAID 6 Out-of-the-box capacity without RAID: 144 TB (12x12 TB) ^a	Recording
RAID	S1148 24 TB Factory RAID level: 5 RAID levels: 0, 1, 5, 6, 10 S1148 64 TB Factory RAID level: 5 RAID levels: 0, 1, 5, 6, 10 S1148 140 TB Factory RAID level: 6 RAID levels: 0, 1, 5, 6, 10	General
Power	S1148 24 TB 2 x 495 W hot-plug redundant power supplies (included) (100-240 V AC, 6.5 - 3 A, 50/60 Hz) S1148 64 TB 2 x 750 W hot-plug redundant power supplies (included) (100-240 V AC, 10 - 5 A, 50/60 Hz) S1148 140 TB	Operating system
		Microsoft® Windows® 10 IoT Enterprise SAC Built-in operating system recovery: yes Operating system drive: 240 GB SSD
		Operating conditions
		10 °C to 35 °C (50 °F to 95 °F) Humidity 20-80% RH (non-condensing)
		Storage conditions
		-40 °C to 65 °C (-40 °F to 149 °F)
		Approvals
		EMC EN 55032 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3, FCC Part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), RCM AS/NZS CISPR 32 Class A, VCCI Class A, KC KN 32 Class A, KC KN 35 Safety IEC/EN/UL 60950-1, EN 62368-1, NOM, BSMI, EAC
		Dimensions
		681 x 482 x 87 mm (26.82 x 19 x 3.43 in), 2U chassis
		Weight
		S1148 24 TB 20.3 kg (45 lb) S1148 64 TB 22.3 kg (49 lb) S1148 140 TB 26.5 kg (58 lb)
		Included accessories
		Rack rails, 2x C13 to C14 power cords for rack PDU (Wall plug power cords are not included)
		Optional accessories
		Axis desktop terminals For more accessories, see axis.com
		Warranty
		5-year warranty, see axis.com/warranty

a. Prior to Q2 2020: 140 TB (14x10 TB)

AXIS Camera Station

For details about AXIS Camera Station features and functions, see the AXIS Camera Station datasheet on axis.com

Environmental responsibility:

axis.com/environmental-responsibility

For more information please contact:



BOCK OPTRONICS INC.

14 Steinway Blvd., Unit 7
Toronto, Ontario M9W 6M6

Tel: (416) 674-2804
sales@bockoptronics.ca
www.bockoptronics.ca