

AXIS S9002 Mk II

Effective 4K client for server installations

AXIS Camera Station S9002 Mk II Desktop Terminal is an easy-to-install desktop terminal for high-definition surveillance with support for four simultaneous 4K streams. The terminal is preloaded with AXIS Camera Station client and all necessary software and is preconfigured to minimize installation time. With its slim form factor, AXIS S9002 Mk II complements Axis rack servers to create a high-end surveillance workstation. The terminal has validated hardware components, such as graphic card and CPUs and supports four monitors for optimal system overview. AXIS S9002 Mk II includes a 5-year warranty, a keyboard and computer mouse.

- > **Ease of installation**
- > **AXIS Camera Station client included**
- > **Validated high performing hardware**
- > **High-definition surveillance up to four 4K streams**
- > **Extensive support**



AXIS S9002 Mk II

Hardware	
Processor	Intel® Core™ i5
Memory	8 GB
Graphic card	Nvidia® Quadro®
Power	300 W (100 - 240 V AC, 50/60 Hz, 4.2 - 2.1 A)
Connectors	5x USB 3.1 1x USB 3.1 Type-C 4x USB 2.0 2x DisplayPort™ 1.2 (not preferred) 4x Mini DisplayPort™ 1x Ethernet (RJ45) 1 GbE 1x Universal audio jack 1x Audio line out 1x Serial port PS2 Mouse and keyboard ports
Video	
Video streaming	Live view: 4 monitors x 4K full screen at 25 fps 4 monitors x 4 split x 1080p at 20 fps 4 monitors x 9 split x 720p at 15 fps Playback: Limited to 1 monitor but supports the same split scenarios as for live view.
General	
Operating system	Microsoft® Windows® 10 IoT Enterprise SAC Built-in operating system recovery: yes
	Operating system drive: 128 GB SSD
Operating conditions	0 °C to 45 °C (32 °F to 113 °F)
Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F)
Approvals	EMC EN 55032, EN 55024, EN/IEC 61000-3-2, EN/IEC 61000-3-3, EN 50564, EN 62623, FCC Part 15 Subpart B Class B, ICES-003 Class B, VCCI Class B, RCM AS/NZS CISPR 32 Class B, KC KN32 Class B, KN35, Safety IEC/EN/UL 60950-1, EN 62368-1, NOM, BSMI, EAC
Dimensions	292 x 93 x 290 mm (11.5 x 3.67 x 11.42 in)
Weight	5.0 kg (11 lb)
Included accessories	Keyboard (international/US), mouse, 4 x Mini DisplayPort™ to DisplayPort™ adapters
Optional accessories	Axis joysticks and control boards For more accessories, see axis.com
Warranty	5-year warranty, see axis.com/warranty

Environmental responsibility:

axis.com/environmental-responsibility

For more information please contact:



BOCK OPTRONICS INC.

14 Steinway Blvd., Unit 7
Toronto, Ontario M9W 6M6

Tel: (416) 674-2804
sales@bockoptronics.ca
www.bockoptronics.ca

AXIS Camera Station S9101 Mk II Desktop Terminal

Compact client for server installations

AXIS Camera Station S9101 Mk II Desktop Terminal is a complement to Axis recorders to enable quick setup of a surveillance workstation. The terminal is preloaded with an AXIS Camera Station client and preconfigured to minimize installation time. AXIS S9101 Mk II has validated hardware and software components for optimal surveillance experience and includes a 5-year warranty.

- > [Ease of installation](#)
- > [AXIS Camera Station software included](#)
- > [Validated hardware](#)
- > [Extensive support](#)



AXIS Camera Station S9101 Mk II Desktop Terminal

Hardware

Processor	Intel® Pentium®
Memory	8 GB
Graphic card	Intel® UHD Graphics
Power	Max 60 W 100 – 240 V AC, 1.8 A, 50/ 60 Hz 12 V DC, 5 A External power adapter
Connectors	Front side: 2x USB 3.1 1x Audio line in 1x Audio line out Rear side: 2x USB 3.1 1x Ethernet (RJ45) 1 GbE 2x DisplayPort™ 1.2

Video

Video streaming	Live view streaming: 4K monitor in one of the following split scenarios: 1 stream at 4K resolution at 30 fps 4 streams at 1080p resolution at 30 fps 9 streams at 720p resolution at 30 fps 24 streams at 360p resolution at 15 fps With an additional 1080p monitor connected, the frame rates might need to be adjusted. Supports all AXIS Camera Station split scenarios
-----------------	--

Playback (one 4K monitor):

Supports the same split scenarios as live view streaming

General

Operating system	Microsoft® Windows® 10 IoT Enterprise SAC Built-in operating system recovery: yes Operating system drive: 128 GB SSD
Operating conditions	0 °C to 35 °C (32 °F to 95 °F) Humidity 5–95% RH (non-condensing)
Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F)
Approvals	EMC EN 55032, EN 55024, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class B, ICES-3(B)/NMB-3(B), RCM AS/NZS CISPR 32 Class B, VCCI Class B Safety IEC/EN/UL 60950-1, IEC/EN/UL 62368-1
Dimensions	207 x 43 x 207 mm (8.15 x 1.7 x 8.15 in)
Weight	1.8 kg (4 lb)
Optional accessories	Axis joysticks and control boards For more accessories, see axis.com
Warranty	5-year warranty, see axis.com/warranty

Environmental responsibility:

axis.com/environmental-responsibility

For more information please contact:



BOCK OPTRONICS INC.

14 Steinway Blvd., Unit 7
Toronto, Ontario M9W 6M6

Tel: (416) 674-2804
sales@bockoptronics.ca
www.bockoptronics.ca