

VNP-29MC-M/C 5

Integrating Thermoelectric Peltier Cooled
into Nano Stage Pixel Shifting Camera



VNP Series, pixel shifting camera equipped with thermo-electric Peltier (TEC) cooled, is designed not only for applications where extremely high resolution is required but also where high quality image is essential. The TEC maintains the operating temperature of the CCD at up to 15 degrees below ambient temperature to reduce noise significantly. Pixel shifting technology based on a precise piezoelectric stage allows image captures as high as 260 million pixels using the VNP-29MC cameras.

These cameras are ideal for applications such as FPD inspection, document/film scanning, research and scientific imaging.

VIEWWORKS

www.viewworks.com

VNP-29MC-M/C 5

Integrating Thermoelectric Peltier Cooled into Nano Stage Pixel Shifting Camera

Main Features

- Nano Stage Pixel Shifting Mechanism
- Thermoelectric Peltier Cooled
- Extended Resolutions up to 260 Megapixels
- True Color Full Image Resolution
- Improved Fill Factor
- Progressive Scan Interline Transfer CCD Imager
- Flat Field Correction / Pixel Defect Correction

Applications

- Flat Panel Display Inspection
- Electronics and Semiconductor Inspection
- Digitizing and Scanning
- Scientific Imaging



Specifications

Model	VNP-29MC-M/C 5	
Resolution (H × V)	× 1 Mode	6576 × 4384, 28.8M
	× 4 Mode	13152 × 8768, 115.3M
	× 9 Mode	19728 × 13152, 259.5M
Sensor	ON Semiconductor KAI-29050	
Sensor Size(Optical Format)	36.17 mm × 24.11 mm (35 mm)	
Sensor Type	Progressive Scan Interline Transfer CCD	
Pixel Size	5.5 μm × 5.5 μm	
Interface	Camera Link	
Max. Frame Rate (40 MHz)	× 1 Mode	4.8 fps
	× 4 Mode	1.2 fps
	× 9 Mode	0.5 fps
Exposure Time (10 μs step)	1/100000 s – 7 s	
Partial Scan (Max. Speed)	15.2 fps at 1000 Lines	
Pixel Data Format	8 / 10 / 12 bit	
Electronic Shutter	Global Shutter	
Data Output Pixel Clock	40/80 MHz	
Trigger Mode	Free-Run, Overlap, Fast, Double – Programmable Exposure Time and Trigger Polarity	
Dynamic Range	62 dB	
Shift Range	0 ~ 15 μm, 1 nm step	
Shift Resolution	0.001 μm	
Shift Control	Manual Mode or Sequence Mode (4/9 Shot Mono, 4/16/36 Shot Color)	
Shift Latency	< 8 ms	
Cooling Method	Thermoelectric Peltier Cooling	
Cooling Performance	15°C below ambient temperature – Standard cooling with a fan	
Dimension / Weight	94 mm × 120 mm × 183.9 mm, 2.3 kg	
Temperature	Operating: 10°C ~ 40°C, Storage: -40°C ~ 70°C	
Lens Mount	F-mount, Custom mount available upon request	
Power	10~14 V DC, Typ. 26.5 W	
Compliance	CE, FCC, KC	
Configuration Software	Configurator	


VNP-29MC-M/C 5

Integrating Thermoelectric Peltier Cooled into Nano Stage Pixel Shifting Camera

Quantum Efficiency Curves



Ordering Scheme




Connector Specification

Power



1, 2, 3: +12V DC 4, 5, 6: GND
(HR10A-7R-6PB)

Control



1: Trigger IN+ 2: Trigger IN-
3: Strobe OUT-(GND) 4: Strobe OUT+
(HR10A-7R-4S)





Connectors on camera body

VNP-29MC-M/C 5

Integrating Thermoelectric Peltier Cooled into Nano Stage Pixel Shifting Camera

Mechanical Dimensions

Unit: mm



For more information please contact:



BOCK OPTRONICS INC.
14 Steinway Blvd., Unit 7
Toronto, Ontario M9W 6M6

Tel: (416) 674-2804
sales@bockoptronics.ca
www.bockoptronics.ca

VNP-604MX-M/C 6 H

604 Megapixel Pixel Shifting Camera
Equipped with Thermoelectric Peltier



CoaXPress®

The VNP-604MX-6 H, a pixel shifting camera equipped with thermo-electric Peltier (TEC) cooled, is designed not only for applications where extremely high resolution is required but also where high quality image is essential. The TEC maintains the operating temperature of the image sensor at up to $15 \pm 2^\circ\text{C}$ below ambient temperature to reduce noise significantly. Pixel shifting technology based on a precise piezoelectric stage allows image captures as high as 604 million pixels at 1.5 fps. The CoaXPress interface adopted by this camera supports transmitting image data at up to 25 Gbps using four coaxial cables. This new camera delivers unique and unparalleled performance in the most demanding applications such as FPD, PCB and semiconductor inspections.

VIEWWORKS

www.viewworks.com

VNP-604MX-M/C 6 H

604 Megapixel Pixel Shifting Camera Equipped with Thermoelectric Peltier

Main Features

- Nano Stage Pixel Shifting Mechanism
- Thermoelectric Peltier Cooled – $15 \pm 2^\circ\text{C}$ below
- Extended Resolutions up to 1,359 MP
- CoaXPress Interface
- Electronic Rolling Shutter
- DSNU and PRNU Correction
- Flat Field Correction with Sequencer Control
- Hot Pixel Correction
- Dynamic Defective Pixel Correction

Applications

- Flat Panel Display Inspection
- Electronics Inspection
- Semiconductor Inspection
- Document / Film Scanning



Specifications

	Model	VNP-604MX-M/C 6 H
Resolution (H×V)	1× (1 Shot)	14192 × 10640
	4× (4 Shot)	28384 × 21280
	Sensor	SONY IMX411
	Sensor Size (Diagonal)	53.36 mm × 40.01 mm (66.7 mm)
	Pixel Size	3.76 μm × 3.76 μm
	Interface	CoaXPress
Max. Frame Rate	1× Mode	6.2 fps (with Overlapped Acquisition)
	4× Mode	1.5 fps (with Overlapped Acquisition)
	Exposure Time (1 μs step)	1 μs – 60 s
	Partial Scan (Max. Speed)	546.4 fps at 2 Lines (12 bit)
Pixel Data Format	Mono	Mono 8 / Mono 10 / Mono 12
	Color	RG Bayer 8 / RG Bayer 10 / RG Bayer 12
	Electronic Shutter	Rolling Shutter
Trigger Synchronization	Overlapped Acquisition	Free-Run
	Non-overlapped Acquisition	Hardware Trigger, Software Trigger or CXP
	Dynamic Range	78 dB
	Gain Control	1× ~ 32×
	Black Level Control	0 ~ 255 LSB at 12 bit
	Shift Range	0 ~ 15 μm , 1 nm step
	Shift Resolution	0.001 μm
	Shift Control	Manual Mode or Sequence Mode (4/9 Shot Mono, 4/16/36 Shot Color)
	Shift Latency	< 5 ms
	Cooling Method	Thermoelectric Peltier Cooling
	Cooling Performance	$15 \pm 2^\circ\text{C}$ below ambient temperature – Standard cooling with a fan
	Dimension / Weight	110 mm × 110 mm × 134 mm, 2.5 kg (with M-72 mount)
	Temperature	Operating: 0°C ~ 40°C , Storage: -40°C ~ 70°C
	Lens Mount	M72-mount, Custom mount available upon request
Power	External	11 ~ 24 V DC
	Dissipation	Typ. 31.0 W
	Compliance	CE, FCC, KC
	API SDK	Vieworks Imaging Solution 7.X


VNP-604MX-M/C 6 H

604 Megapixel Pixel Shifting Camera Equipped with Thermoelectric Peltier

Spectral Response



Ordering Scheme




Connector Specification

Power




1, 2, 3: +12 V DC
4, 5, 6: GND
(HR10A-7R-6PB)

Control



1: Trigger IN+
2: Trigger IN-
3: Strobe Out-(GND)
4: Strobe Out+
(HR10A-7R-4S)

Data Transfer / Communications



CH1: Master Connection
75 Ω, DIN 1.0/2.3


Connectors on camera body

VNP-604MX-M/C 6 H

604 Megapixel Pixel Shifting Camera Equipped with Thermoelectric Peltier

Mechanical Dimensions

Unit: mm



For more information please contact:



BOCK OPTRONICS INC.
14 Steinway Blvd., Unit 7
Toronto, Ontario M9W 6M6

Tel: (416) 674-2804
sales@bockoptronics.ca
www.bockoptronics.ca

VNP-200MX

200 MEGAPIXEL PIXEL SHIFTING CAMERA
EQUIPPED WITH THERMOELECTRIC PELTIER



CoaXPress®

The VNP-200MX, a pixel shifting camera equipped with thermo-electric Peltier (TEC) cooled, is designed not only for applications where extremely high resolution is required but also where high quality image is essential. The TEC maintains the operating temperature of the image sensor at up to 10 degrees below ambient temperature to reduce noise significantly. Pixel shifting technology based on a precise piezoelectric stage allows image captures as high as 427 million pixels using the VNP-200MX camera. Its CoaXPress interface supports transmitting image data at up to 25 Gbps using four coaxial cables. This camera is ideal for applications such as FPD inspection, document / film scanning, research and scientific imaging.

VNP-200MX

200 MEGA PIXEL PIXEL SHIFTING CAMERA EQUIPPED WITH THERMOELECTRIC PELTIER

Main Features

- * 50 Megapixel Resolution (AMS CMOSIS)
- * Nano Stage Pixel Shifting Mechanism
- * Extended Resolution up to 427 MP at 3 fps (9 Shot Mode)
- * Thermoelectric Peltier Cooling
- * CoaXPress Interface up to 30 fps at 25 Gbps using 4 CH
- * Pixel Defect Correction
- * Flat Field Correction
- * DSNU and PRNU Correction

Applications

- * FPD and PCB Inspection
- * Semiconductor Inspection
- * High Speed 3D Imaging
- * Digitizing and Scanning
- * Research and Scientific Imaging


Specifications

Model	VNP-200MX-M/C 30			
Resolution (H × V)	7920 × 6004			
Sensor	AMS CMOSIS CMV 50000			
Sensor Size	36.43 mm × 27.62 mm (Diagonal: 45.72 mm, Optical Format: 35 mm)			
Sensor Type	High Speed CMOS Image Sensor			
Pixel Size	4.6 μm × 4.6 μm			
Interface	CoaXPress			
Max. Frame Rate	47.5 MP	1CH: 7.7 fps @ 6.25 Gbps	2CH: 15.5 fps @ 6.25 Gbps	4CH: 30.9 fps @ 6.25 Gbps
	190 MP	1CH: 2 fps @ 6.25 Gbps	2CH: 3.9 fps @ 6.25 Gbps	4CH: 7.7 fps @ 6.25 Gbps
	427 MP	1CH: 1 fps @ 6.25 Gbps	2CH: 1.7 fps @ 6.25 Gbps	4CH: 3.4 fps @ 6.25 Gbps
Exposure Time (1 μs step)	1 μs – 60 s			
Partial Scan (Max. Speed)	3968 fps at 4 Lines			
Pixel Data Format	Mono	Mono 8 / Mono 10 / Mono 12		
	Color	BG Bayer 8 / BG Bayer 10 / BG Bayer 12		
Electronic Shutter	Global Shutter			
Exposure Mode	Free-Run, Timed and Trigger Width			
Dynamic Range	64 dB			
Gain Control	1 × ~ 30 × (1/1024 step)			
Black Level Control	0 ~ 256 LSB at 12 bit (1 LSB step)			
Shift Range	0 ~ 7.5 μm, 1 nm step			
Shift Resolution	0.001 μm			
Shift Control	Sequence Mode (mono4, mono9, mono2H, mono2V, bayer4, bayer16)			
Cooling Method	Thermoelectric Peltier Cooling			
Cooling Performance	10°C below ambient temperature / Standard cooling with a fan			
Dimension / Weight	90 mm × 90 mm × 191 mm, 1,920 g			
Temperature	Operating: -5°C ~ 40°C, Storage: -40°C ~ 70°C			
Lens Mount	F-mount, Custom mount available upon request			
Power	External	10 ~ 24 V DC, Typ. 26.0 W		
	PoCXP	Not supported		
Compliance	CE, FCC, KC			
API SDK	Vieworks Imaging Solution 7.X			


VNP-200MX

200 MEGAPIXEL PIXEL SHIFTING CAMERA EQUIPPED WITH THERMOELECTRIC PELTIER


Quantum Efficiency Curves



Ordering Scheme



Connector Specification




Connectors on camera body

VNP-200MX


200 MEGA PIXEL PIXEL SHIFTING CAMERA EQUIPPED WITH THERMOELECTRIC PELTIER

Mechanical Dimensions


Unit: mm




<Front View>



<Top View>



<Back View>



<Side View>

For more information please contact local distributor or visit our website at <http://www.vieworks.com>.

Reproduction in whole or in part without written permission is prohibited. Vieworks Co., Ltd. is not responsible for any technical or typographical errors and reserves the right to make changes to products, specifications and documentation without prior notice.

D-18-206

For more information please contact:



BOCK OPTRONICS INC.
14 Steinway Blvd., Unit 7
Toronto, Ontario M9W 6M6

Tel: (416) 674-2804
sales@bockoptronics.ca
www.bockoptronics.ca

VIEWWORKS

41-3, Burim-ro 170 beon-gil, Dongan-gu, Anyang-si, Gyeonggi-do, 14055 Republic of Korea
tel +82-70-7011-6161 fax +82-31-386-8631 e-mail sales@vieworks.com

VNP-190MX

190 MEGAPIXEL PIXEL SHIFTING CAMERA
EQUIPPED WITH THERMOELECTRIC PELTIER



CoaXPress®

The VNP-190MX, a pixel shifting camera equipped with thermo-electric Peltier (TEC) cooled, is designed not only for applications where extremely high resolution is required but also where high quality image is essential. The TEC maintains the operating temperature of the image sensor at up to 14 degrees below ambient temperature to reduce noise significantly. Pixel shifting technology based on a precise piezoelectric stage allows image captures as high as 420 million pixels using the VNP-190MX camera. Its CoaXPress interface supports transmitting image data at up to 12.5 Gbps using two coaxial cables. This camera is ideal for applications such as FPD inspection, document / film scanning, research and scientific imaging.

VIEWWORKS