

# **Nocturn Series**



HIGH RESOLUTION LOW LIGHT CAMERA IN THE VISIBLE & NIR

### **KEY FEATURES**



**LOW LIGHT CMOS SENSOR** 



**UP TO 100 FPS** 



**DAY & NIGHT IMAGING** 



LASER DETECTION (860nm & 1064nm)

The Nocturn series is ruggedized passive low-light camera that features high-definition, high sensitivity and high dynamic range with low power consumption

Its small size, weight and power (SWaP) makes these camera cores ideal for integration into aerial, vehicle and hand-held surveillance systems

The Nocturn series is available in different video interfaces such as HD-SDI, CameraLink or PAL/NTSC, USB 3.0 and LVCMOS



# **Nocturn Series**

LOW READ NOISE (LESS THAN 4e<sup>-</sup>)

HIGH DYNAMIC RANGE



VARIOUS VIDEO **♦ INTERFACES** 



HD-SDI



CameraLink or PAL/NTSC



**LVCMOS** 



**USB 3.0** 

### **KEY PERFORMANCE**

Sensor	CMOS low light sensor in monochrome or color
Resolution	1280 x 1024 pixels
Pixel Pitch	9.7 μm x 9.7 μm
Spectral Range	350 – 1100 nm
Frame Rate	Up to 100 fps
Sensitivity	Full daylight to quarter moon condition (NL3)

## <

## FUNCTIONS & INTERFACES

Image enhancement	Non-uniformity correction, noise removal, sharpening
Image processing	Noise removal, sharpening, contrast enhancement
Digital Zoom	Up to 8x (depend on type)
Video output	HD-SDI / CameraLink, PAL-NTSC / LVCMOS / USB 3.0
Dimensions	From 34.1 x 036.6 x 37.4 mm <sup>3</sup> (depend on type)
Weight	From 85 g (depend on type)
Communication	Serial over USB or TS-422

## ENVIRONMENT & POWER

Operating temperature	-40°C to +60°C (depend on type)
Storage temperature	-50°C to +80°C (depend on type)
Input voltage	+5 to +12 VDC over GPIO interface

### **Applications**

- Armored vehicles & platform sights
- ♦ Scientific instrumentation
- Advanced medical imaging
- Machine vision
- Surveillance

For more information please contact:

#### **BOCK OPTRONICS INC.**

14 Steinway Blvd., Unit 7 Toronto, Ontario M9W 6M6

Tel: (416) 674-2804 sales@bockoptronics.ca www.bockoptronics.ca

□ The data shown in the table is subject to the Nocturn type





advancedimaging@exosens.com

