

**WORLD'S FASTEST InGaAs
AREA-SCAN CAMERA**

Xenics
EXOSENS GROUP

Cheetah Series



*WORLD'S FASTEST InGaAs AREA-SCAN CAMERA
WITH HIGH IMAGE RESOLUTION*

KEY FEATURES



**WORLD'S FASTEST SWIR AREA-
SCAN IMAGING UP TO 1700 Hz**



HIGH-QUALITY IMAGE



**STATE-OF-THE-ART SWIR
PERFORMANCE**

The Cheetah series is based on an in-house developed, temperature stabilized InGaAs detector with a 640 x 512 pixel resolution. The Cheetah 640 camera with single-stage TE-cooled detector offers high frame rates of either 400 Hz, 800 Hz or 1700 Hz while the version with three-stage TE-cooled detector offers a frame rate of up to 110 Hz.

A visible short-wave infrared (vSWIR) option is available for extension into the visible wavelength band.



Cheetah Series



KEY PERFORMANCES

Image format / Pixel pitch	640 x 512 pixels/ 20 μ m
Detector type	InGaAs photodiode array with CTIA ROIC
Sensor cooling	TE-cooled
Integration type	Snapshot - global shutter
Spectral range	900 - 1700 nm (SWIR); 500 - 1700 nm (vSWIR)
Max frame rate (full frame)	111 Hz / 444 Hz / 865 Hz / 1730 Hz
Power consumption	Up to 25 W or 60 W
Power supply voltage	DC 12 V

FUNCTIONS & INTERFACES

Command and control	CameraLink
Connector trigger	SMA
Camera dimensions (width x height x length)	143 mm x 137 mm x 95 mm
Optical interface	C-mount
Camera weight	2000 gr

PRODUCT SELECTOR GUIDE

XEN-000175 (Cheetah 640 TE1 400)	XEN-000045 (Cheetah 640 TE1 400 vSWIR)
XEN-000577 (Cheetah 640 TE1 800)	XEN-000578 (Cheetah 640 TE1 800 vSWIR)
XEN-000176 (Cheetah 640 TE1 1700)	XEN-000046 (Cheetah 640 TE1 1700 vSWIR)
XEN-000271 (Cheetah 640 TE3)	

advancedimaging@exosens.com



exosens.com

EXOSENS
REVEAL THE INVISIBLE

© Xenics. The information furnished is believed to be accurate and reliable, but is not guaranteed and is subject to change without notice. No liability is assumed by Xenics nor by any Exosens Group companies. Performance data represents typical characteristics as individual product performance may vary. Customers should verify that they have the most current Xenics product information before placing orders. Texts and pictures may not be considered as contractually binding. This document may not be reproduced, in whole or in part, without the prior written consent of Xenics.

**WORLD'S FASTEST SWIR
InGaAs AREA-SCAN CAMERA**

Xenics
EXOSENS GROUP

Cheetah+ 640 Series



*WORLD'S FASTEST SWIR InGaAs AREA-SCAN
CAMERA WITH HIGH IMAGE RESOLUTION*

KEY FEATURES



**WORLD'S FASTEST SWIR AREA-
SCAN IMAGING UP TO 1700 Hz**



HIGH-QUALITY IMAGE



**STATE-OF-THE-ART SWIR
PERFORMANCE**

The Cheetah+ series is based on an in-house developed, temperature stabilized InGaAs detector with a 640 x 512 pixel resolution. The Cheetah+ 640 offers high frame rates of 1700 Hz.

With its unique features of high-speed, high-resolution, and best sensitivity in a reliable InGaAs array, the Cheetah+ cameras are perfectly suited for high-speed imaging in the SWIR range for a variety of demanding applications.



Cheetah+ 640 Series



KEY PERFORMANCES

Image format / Pixel pitch	640 x 512 pixels/ 20 μ m
Detector type	InGaAs photodiode array with CTIA ROIC
Sensor cooling	TE1
Integration type	Snapshot - global shutter
Spectral range	900 - 1700 nm
Max frame rate (full frame)	1700 Hz
Power consumption (with cooling)	25.2 W (via power supply), 15.3 W (via CXP)
Power consumption (without cooling)	12.5 W
Power supply voltage	DC 24 V

FUNCTIONS & INTERFACES

Command and control	CXP
Connector trigger	via unified connector
Camera dimensions (width x height x length)	100mm x 100mm x 73mm (OEM) 108mm x 108mm x 73mm (CAM)
Optical interface (optional)	C-mount
Camera weight	875 gr (OEM) 1206 gr (CAM)

PRODUCT SELECTOR GUIDE

XEN-000946 (Cheetah+ 640 CXP OEM 1700)	XEN-000947 (Cheetah+ 640 CXP CAM 1700)
--	--



For more information please contact:

BOCK OPTONICS INC.
14 Steinway Blvd., Unit 7
Toronto, Ontario M9W 6M6

Tel: (416) 674-2804
sales@bockoptronics.ca
www.bockoptronics.ca



exosens.com

EXOSENS
REVEAL THE INVISIBLE